

ADHESIVE C-200**Adhesive for paper and additive to building materials**

PURPOSE:	
Adhesive for paper and additive to cement and gypsum solutions. Do not mix with other similar products, and application at temperatures lower than 5°C and higher than 35°C.	
QUALITIES:	
<ul style="list-style-type: none">- Produced with German polyvinyl acetate dispersion- High adhesion strength- Plasticized building solutions by increasing the open time and facilitates their application- Does not contain mineral fillers (chalk, vinervays). It forms a transparent film- Correspond to the Bulgarian and European legislation	
CLASSIFICATION:	
-	
TECHNICAL DATA OF THE PRODUCT:	
Appearance after stirring: (visually)	Homogeneous, thick mass.
Non- volatile substances content, at (125±2)°C/2h (BS EN ISO 3251)	min 45%
Density: (BS EN ISO 2811-1)	1,00 - 1,05 kg/l
CONSUMPTION RATE:	
Depending on the base	
SHELF LIFE:	
24 months from the production date in fabrically closed packages.	
PACKAGING:	
Plastic packages with a net weight of 0,5kg; 1,0kg; 3,5kg; 10,0kg; 18,0kg. It is possible to use and other packaging after prior agreement with the client.	
COLOUR:	
Milky white. It forms a transparent film.	
STORAGE:	
Store in covered and dry warehouses at 5 ⁰ C to 40 ⁰ C, protect from direct sunlight. Warning! Protect from freezing during storage and transport! P102 - Keep out of reach of children. P262 - Avoid contact with eyes, skin or clothing. P301 + P310 - In swallowed immediately call a POISON CENTER or doctor. P273 - Avoid release to the environment.	
DILUENT:	
Water, if necessary.	
PREPARATION OF THE BASE:	
The base should be dry and dedusted.	
SUITABLE BASES:	
<ul style="list-style-type: none">- Additive to construction solutions	

- Paper
For other bases, please consult us!
UNSUITABLE BASES:
- Wood surfaces - Glass surfaces - Metal surfaces - Plastic surfaces
APPLICATION INSTRUMENTS:
Putty-knife.
CLEANING OF THE INSTRUMENTS:
With water before they are dry.
APPLICATION CONDITIONS:
- It is applied at temperatures not lower than 7 °C and not higher than 35 °C. - Do not mix with other similar products.
WAY OF WORKING:
The adhesive is stirred before use. As an adhesive for paper is applied unilaterally in the thin film as open time depends on the type of adhesions material. As a plasticizer for mortars is added from 1% to 3% depending on the properties required. Do not use at a temperature lower than 7 °C.
HYGIENE AND SAFE WORK:
The product is not classified as dangerous. If necessary, refer to the Safety Data Sheet.