

**BOROTHERM 67****Adhesive for thermal insulation boards, depron, selitron, polystyrene foam, etc.****FOR INTERIOR APPLICATION**

<b>PURPOSE:</b>	
Adhesive for ceramic and terracotta tiles, small and medium mosaic tiles, insulation boards of soft and hard foamed plastics. Can be used on plasters, gypsum barrier boards, plasterboard, aerated concrete and other absorbent materials. Designed for indoor use. Do not mix with other similar products, and application at temperatures lower than 5°C and higher than 35°C.	
<b>QUALITIES:</b>	
<ul style="list-style-type: none"><li>- Easy to apply with high initial adhesion and high strength adhesive</li><li>- High resistance to moisture</li><li>- Very good elasticity</li><li>- Correspond to the Bulgarian and European legislation</li></ul>	
<b>CLASSIFICATION:</b>	
-	
<b>TECHNICAL DATA OF THE PRODUCT:</b>	
<b>Appearance after stirring:</b> (visually)	Homogeneous, thick mass.
<b>Non- volatile substances content, at (125±2)°C/2h</b> (BS EN ISO 3251)	min 72%
<b>Density:</b> (BS EN ISO 2811-1)	1,68 - 1,70 kg/l
<b>pH value:</b> (pH-meter)	min 8,0
<b>Appearance of the film:</b> (visually)	flat, smooth, matt
<b>Drying:</b> at (23 ± 0,5)°C, 65% H.R	air dry to the touch 2-3 h
<b>CONSUMPTION RATE:</b>	
Depending on the base.	
<b>SHELF LIFE:</b>	
24 months from the production date in fabrically closed packages.	
<b>PACKAGING:</b>	
Plastic packages with a net weight of 1,5 kg; 5 kg; 15kg. It is possible to use and other packaging after prior agreement with the client.	
<b>COLOUR:</b>	
Produced in white.	
<b>STORAGE:</b>	
Store in covered and dry warehouses at 5 <sup>0</sup> C to 40 <sup>0</sup> C, protect from direct sunlight. <b>Warning! Protect from freezing during storage and transport!</b> <b>P102</b> - Keep out of reach of children. <b>P262</b> - Avoid contact with eyes, skin or clothing. <b>P301 + P310</b> - In swallowed immediately call a POISON CENTER or doctor.	

<b>P273</b> - Avoid release to the environment.
<b>DILUENT:</b>
Ready for use. Do not dilute.
<b>PREPARATION OF THE BASE:</b>
The base should be dry, clean and healthy. Friable surfaces should be cleaned mechanically. Damaged and friable old coatings and plasters are removed until a strong base and spots are patched. Covered with mold surfaces treated with <b>Boro remediation concentrate</b> . Absorbent surfaces are primed with <b>Boroprimer deeply penetrating</b> – concentrate or for direct use. New lime putties and sand plasters painted at least three months after drying.
<b>SUITABLE BASES:</b>
<ul style="list-style-type: none"><li>- Cement, lime-cement, sand plasters</li><li>- Concrete surfaces</li><li>- Gypsum plasters and putties</li><li>- Plasterboard and gypsum fibreboard</li><li>- Aerated concrete</li><li>- Old latex coatings</li></ul>
<b>For other bases, please consult us!</b>
<b>UNSUITABLE BASES:</b>
<ul style="list-style-type: none"><li>- Glass surfaces</li><li>- Metal surfaces</li><li>- Plastic surfaces</li></ul>
<b>APPLICATION INSTRUMENTS:</b>
- Notched trowel, roller
<b>CLEANING OF THE INSTRUMENTS:</b>
With water before they are dry.
<b>APPLICATION CONDITIONS:</b>
<ul style="list-style-type: none"><li>- It is applied at temperatures not lower than 7 °C and not higher than 35 °C.</li><li>- Do not mix with other similar products.</li></ul>
<b>WAY OF WORKING:</b>
The adhesive is stirred before use. <b>When laying wallpaper:</b> using a notched trowel size teeth 2 mm or brush applied a uniform layer of adhesive on the surface to be stick with wallpapers for 10-20 minutes. The wallpaper is placed on the wall and pressed hard. Use wallpaper roller to ensure uniform bonding. <b>When laying slabs and panels:</b> The adhesive may be applied at point of 5 to 9 seats on the opposite side of plane, and it is pressed against the foundation.
<b>HYGIENE AND SAFE WORK:</b>
The product is not classified as dangerous. If necessary, refer to the Safety Data Sheet.